

Trimble S5

TOTAL STATION

Trusted Performance

All you need to perform efficient surveying campaigns is available in the Trimble® S5 Total Station solution: An accurate and reliable instrument, DR Plus EDM, MagDrive™ technology, with Trimble Access™ field software on your choice of Trimble data collector and quick data processing with Trimble Business Center office software.

Trimble has been manufacturing the industry's leading robotic total stations for over a decade. You can depend on the Trimble S5 Total Station to keep you productive in the field no matter what you encounter.

Trimble Technology

The Trimble S5 Total Station is built upon proven Trimble technologies like SurePoint™ technology, MagDrive and our DR Plus EDM, helping you work more efficiently while maintaining the highest accuracy possible. Smooth and silent, Trimble MagDrive electro-magnetic technology means fewer moving parts. Trimble SurePoint ensures accurate pointing and measurements by actively correcting for unwanted movements like wind, handling, and sinkage. The Trimble DR Plus EDM allows you to measure with fewer instrument set-ups and enhance your direct reflex performance.

The Trimble S5 Total Stations are available in robotic or Autolock® versions.

Trimble S5 Configurations

EDM	ANGLE ACCURACY	SERVO CONTROL	ACTIVE TRACK
DR Plus	1", 2", 3", 5"	Robotic, Autolock	Optional

Integrated Surveying

The Trimble S5 Total Station provides the foundation for Trimble's Integrated Surveying™ software. With Integrated Surveying, you can seamlessly integrate complementary technologies on the job site, such as Trimble GNSS receivers and optical measurements.

Manage Your Assets 24/7

Know where your total stations are 24 hours a day with Trimble Sentinel technology. See where your equipment is at any given time and get alerts if your instrument leaves a jobsite or experiences unexpected equipment shock or abuse.

Powerful Field and Office Software

Choose from a variety of Trimble controllers operating the feature rich, intuitive Trimble Access field software. Streamlined workflows guide crews through common project types, helping to get the job done faster with less distractions. Trimble Access workflows can also be customised to fit your needs.

Back in the office, trust Trimble Business Center software to help you check, process and adjust your optical, levelling, and GNSS data in one software solution. No matter what Trimble instruments you use in the field, you can trust that Trimble Business Center office software will help you generate industry-leading deliverables.



Key Features

- Everything you need to perform survey campaigns
- Measure further and faster with the Trimble DR Plus EDM
- Trimble Sentinel real-time location information
- Intuitive Trimble Access Field Software
- Trimble Business Center Office Software for quick data processing

Trimble S5

Total station



SYSTEM SPECIFICATIONS

LASER CLASS

EDM	Laser class 1
Laser pointer coaxial (standard)	Laser class 2
Overall product laser class	Laser class 2

LEVELLING

Circular level in tribrach	8/2 mm (8/0.007 ft)
Electronic 2-axis level in the LC-display with a resolution of	0.3" (0.1 mgon)

SERVO SYSTEM

MagDrive servo technology, integrated servo/angle sensor electromagnetic direct drive	Rotation speed	115 degrees/sec (128 gon/sec)
	Rotation time Face 1 to Face 2	2.6 sec
	Positioning time 180 degrees (200 gon)	2.6 sec
	Clamps and slow motions	Servo-driven, endless fine adjustment

CENTRING

Centring system	Trimble 3-pin
Optical plummet	Built-in optical plummet
Magnification/shortest focusing distance	2.3×/0.5 m–infinity (1.6 ft–infinity)

TELESCOPE

Magnification	30×
Aperture	40 mm (1.57 in)
Field of view at 100 m (328 ft)	2.6 m at 100 m (8.5 ft at 328 ft)
Shortest focusing distance	1.5 m (4.92 ft)–infinity
Illuminated crosshair	Variable (10 steps)

POWER SUPPLY

Rechargeable Li-Ion battery	10.8 V, 6.5 Ah	
Operating time ⁶	One internal battery	up to 7.5 hours
	Three batteries in multi-battery adapter and one internal	up to 30 hours

WEIGHT AND DIMENSIONS


Instrument (Autolock)	5.4 kg (11.35 lb)
Instrument (Robotic)	5.5 kg (11.57 lb)
Trimble TCU5 controller	0.44 kg (0.97 lb)
Tribrach	0.7 kg (1.54 lb)
Internal battery	0.35 kg (0.77 lb)
Trunnion axis height	196 mm (7.71 in)

OTHER

Communication	USB, Serial, Bluetooth ⁷
Operating temperature	-20 °C to +50 °C (-4 °F to +122 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Tracklight	Standard in all models
Dust and water proofing	IP65
Humidity	100% Condensing
Security	Dual-layer password protection, Sentinel ¹⁰

Trimble S5


Total station



PERFORMANCE					
ANGLE MEASUREMENT					
Sensor type	Absolute encoder with diametrical reading				
Accuracy ¹	1" (0.3 mgon)				
	2" (0.6 mgon), 3" (1.0 mgon), or 5" (1.5 mgon)				
Display (least count)	0.1" (0.01 mgon)				
Automatic level compensator	Type	Centred dual-axis			
	Accuracy	0.5" (0.15 mgon)			
	Range	±5.4' (±100 mgon)			
DISTANCE MEASUREMENT					
Accuracy (ISO)	Prism mode	Standard ²	1 mm + 2 ppm (0.003 ft + 2 ppm)		
Accuracy (RMSE)	Prism mode	Standard	2 mm + 2 ppm (0.0065 ft + 2 ppm)		
		Tracking	4 mm + 2 ppm (0.013 ft + 2 ppm)		
	DR mode	Standard	2 mm + 2 ppm (0.0065 ft + 2 ppm)		
		Tracking	4 mm + 2 ppm (0.013 ft + 2 ppm)		
		Extended range	10 mm + 2 ppm (0.033 ft + 2 ppm)		
MEASURING TIME					
	Prism mode	Standard	1.2 sec		
		Tracking	0.4 sec		
	DR mode	Standard	1-5 sec		
		Tracking	0.4 sec		
MEASUREMENT RANGE					
	Prism mode (under standard clear conditions ^{3,4})	1 prism	2,500 m (8,202 ft)		
		1 prism Long Range mode	5,500 m (18,044 ft) (max. range)		
		Shortest possible range	0.2 m (0.65 ft)		
	DR mode		Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate unlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
			White card (90% reflective) ⁵	1,300 m (4,265 ft)	1,300 m (4,265 ft)
		Grey card (18% reflective) ⁵	600 m (1,969 ft)	600 m (1,969 ft)	550 m (1,804 ft)
		Reflective foil 60x60 mm			1,200 m (3,937 ft)
		Shortest possible range			1 m (3.28 ft)
	DR Extended Range Mode	White Card (90% reflective) ⁵			2,200 m (7,218 ft)
	EDM SPECIFICATIONS				
Light source	Pulsed laserdiode 905 nm				
Beam divergence	Horizontal	4 cm/100 m (0.13 ft/328 ft)			
	Vertical	8 cm/100 m (0.26 ft/328 ft)			

Trimble S5

Total station



ROBOTIC SURVEYING

Autolock and Robotic Range ⁴	Passive prisms	700 m (2,297 ft)
	Trimble MultiTrack™ Target	800 m (2,625 ft)
	Trimble Active Track 360 target	500 m (1,640 ft)
Autolock pointing precision at 200 m (656 ft) (Standard deviation) ³	Passive prisms	<2 mm (0.007 ft)
	Trimble MultiTrack target	<2 mm (0.007 ft)
	Trimble Active Track 360 target	<2 mm (0.007 ft)
Shortest search distance	0.2 m (0.65 ft)	
Type of radio internal/external	2.4 GHz frequency-hopping, spread-spectrum radios	
Search time (typical) ⁸	2-10 sec	

GPS SEARCH/GEOLock

GPS Search/GeoLock	360 degrees (400 gon) or defined horizontal and vertical search window	
Solution acquisition time ⁹	15-30 sec	
Target re-acquisition time	<3 sec	
Range	Autolock & Robotic range limits	

- 1 Standard deviation according to ISO17123-3.
- 2 Standard deviation according to ISO17123-4.
- 3 Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.
- 4 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
- 5 Kodak Grey Card, Catalog number E1527795.
- 6 The capacity in -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).
- 7 Bluetooth type approvals are country specific. Contact your local Trimble Authorised Distribution Partner for more information.
- 8 Dependent on selected size of search window.
- 9 Solution acquisition time is dependent upon solution geometry and GPS position quality.
- 10 Functionality and availability dependent on region.

Specifications subject to change without notice.

Contact your local Trimble Authorised Distribution Partner for more information

NORTH AMERICA
 Trimble Inc.
 10368 Westmoor Dr
 Westminster CO 80021
 USA

EUROPE
 Trimble Services GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC
 Trimble Navigation
 Singapore PTE Limited
 3 HarbourFront Place
 #13-02 HarbourFront Tower Two
 Singapore 099254
 SINGAPORE

