

Trimble S9/S9 HP

TOTAL STATION

Performance and precision

The Trimble® S9 total stations integrate the best field technologies plus our highest level of accuracy and specialized engineering features for the ultimate in performance and precision. You can combine scanning, imaging and surveying into one solution, or focus on the highest level of accuracy with options such as Long Range FineLock™ technology and our Trimble DR High Precision (HP) EDM for applications where precision is priority. Back in the office, trust our powerful Trimble Business Center software and Trimble 4D Control™ software to help you process and analyze your data.

Specialized for Engineering Applications

The Trimble S9 total station is built for specialized applications such as monitoring and tunneling, where you need a solution with optimal speed, accuracy and reliability. Combine the Trimble DR HP EDM in the S9 HP with your choice of 1" or 0.5" angular accuracies and Long Range FineLock and you have the flexibility to tackle the most demanding projects.

Trimble DR Plus and DR HP EDM

Trimble DR Plus range measurement technology provides extended range of Direct Reflex measurement without a prism to exceptionally long distances, while the Trimble DR HP EDM in the Trimble S9 HP offers higher accuracy when measuring to prisms. Trimble's high performance EDMs, combined with the smooth and frictionless drive capabilities of Trimble MagDrive™ servo technology, creates unmatched capability for quick measurements, without compromising on accuracy.

Advanced Engineering Features

Additional engineering-specific features in the Trimble S9 total stations include Trimble FineLock technology. Trimble FineLock detects targets without interference from surrounding prisms for high precision applications in close quarters. The Trimble Long Range FineLock option extends this functionality.

Manage Your Assets 24/7

Know where your total stations are 24 hours a day with Trimble L2P technology. See where your equipment is at any given time and get alerts if your instrument leaves a job site or experiences unexpected equipment shock or abuse.

Trimble AllTrak™ software lets you view usage and keep up-to-date on firmware, software and maintenance requirements. With Trimble L2P and AllTrak, you can rest assured knowing your equipment is up-to-date and where it should be.

Trimble VISION and SureScan Technology

The Trimble S9 comes with optional Trimble VISION™ and Trimble SureScan™ technology. The improved Trimble VISION gives you the power direct your survey with live video images on the controller as well as create a wide variety of deliverables from collected imagery. Trimble SureScan in the Trimble S9 total station provides the flexibility to perform feature-rich scans every day, without the complexity of setting up a separate scanning system or switching to specialized field software. Trimble SureScan ensures that you have even coverage and get the most efficiency from your scanning.

Powerful Field and Office Software

Trimble controllers and our specialized modules in Trimble Access™ field software such as Tunnels, Monitoring, Pipelines and Mines provide dedicated workflows to help you get the job done faster. Trimble Access workflows can also be customized to fit your needs.

In the office, use Trimble Business Center to help you check, process and adjust your data in one software solution. Trimble 4D Control office software provides a comprehensive solution for the management of monitoring projects—both real-time and post-processed—to rapidly detect critical structural movements.




Key Features

- Available 0.5" or 1" angle accuracy
- Trimble DR Plus or HP EDM for optimal speed, accuracy and reliability
- Optional Trimble VISION and SureScan technology
- Trimble L2P real-time equipment management
- Intuitive Trimble Access Field Software
- Trimble Business Center Office Software for quick data processing
- Trimble 4D Control for monitoring management

Trimble S9/S9 HP

Total station



TRIMBLE S9 AND S9 HP CONFIGURATIONS

	EDM	Accuracy	Servo	Trimble VISION	Sure Scan	FineLock	Long Range FineLock	Tracklight
S9	DR Plus	0.5"	Robotic	Yes	Yes	Yes	No	No
	DR Plus	0.5"	Robotic	No	No	Yes	Yes	No
	DR Plus	0.5"	Robotic	No	No	Yes	No	Yes
	DR Plus	1"	Robotic or Autolock®	No	No	Yes	Yes	No
S9 HP	DR HP	0.5"	Robotic	No	No	Yes	Yes	No
	DR HP	0.5"	Robotic or Autolock	No	No	Yes	No	Yes
	DR HP	0.5"	Robotic	Yes	No	Yes	No	No
	DR HP	1"	Robotic or Autolock	Yes	No	Yes	No	No
	DR HP	1"	Robotic or Autolock	No	No	Yes	No	Yes
	DR HP	1"	Robotic or Autolock	No	No	Yes	Yes	No
	DR HP	1"	Robotic	No	No	Yes	No	No

PERFORMANCE (DR PLUS)

ANGLE MEASUREMENT								
Sensor type	Absolute encoder with diametrical reading							
Accuracy ¹	0.5" (0.15 mgon) or 1" (0.3 mgon)							
Display (least count)	0.1" (0.01 mgon)							
Automatic level compensator	Type	Centered dual-axis						
	Accuracy	0.5" (0.15 mgon)						
	Range	±5.4' (±100 mgon)						
DISTANCE MEASUREMENT								
Accuracy (ISO)	Prism mode	Standard ²	1 mm + 2 ppm (0.003 ft + 2 ppm)					
Accuracy (RMSE)	Prism mode	Standard	2 mm + 2 ppm (0.0065 ft + 2 ppm)					
		Tracking	4 mm + 2 ppm (0.013 ft + 2 ppm)					
	DR mode	Standard	2 mm + 2 ppm (0.0065 ft + 2 ppm)					
		Tracking	4 mm + 2 ppm (0.013 ft + 2 ppm)					
	Extended Range		10 mm + 2 ppm (0.033 ft + 2 ppm)					
MEASURING TIME								
	Prism mode	Standard	1.2 s					
		Tracking	0.4 s					
	DR mode	Standard	1–5 s					
		Tracking	0.4 s					
MEASUREMENT RANGE								
	Prism mode (under standard clear conditions ^{3,4})	1 prism	2,500 m (8,202 ft)					
		1 prism Long Range mode	5,500 m (18,044 ft) (max. range)					
		Shortest range	0.2 m (0.65 ft)					
	DR mode	White card (90% reflective) ⁵	Good (Good visibility, low ambient light)	1,300 m (4,265 ft)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	1,300 m (4,265 ft)	Difficult (Haze, object in direct sunlight, turbulence)	1,200 m (3,937 ft)
			Gray card (18% reflective) ⁵	600 m (1,969 ft)	600 m (1,969 ft)	550 m (1,804 ft)		
		Reflective foil 20 mm	1000 m (3280 ft)					
		Shortest possible range	1 m (3.28 ft)					
		DR Extended Range Mode	White Card (90% reflective) ⁵	2200 m				
SCANNING								
	Range ^{3,4}	from 1 m up to 250 m (3.28 ft–820 ft)						
	Speed	up to 15 points/sec						
	Minimum point spacing	10 mm (0.032 ft)						
	Standard deviation	1.5 mm @ ≤50 m (0.0049 ft @ ≤164 ft)						
	Single 3D point accuracy	10 mm @ ≤150 m (0.032 ft @ ≤492 ft)						

EDM SPECIFICATIONS (DR PLUS)

Light source	Pulsed laserdiode 905 nm		
Beam divergence	Horizontal	4 cm/100 m (0.13 ft/328 ft)	
	Vertical	8 cm/100 m (0.26 ft/328 ft)	


Trimble S9/S9 HP

Total station

PERFORMANCE (DR HP)				
Sensor type	Absolute encoder with diametrical reading			
Angle measurement	Angle accuracy ¹	0.5" (0.15 mgon) or 1" (0.3 mgon)		
	Angle display (least count)	0.1" (0.01 mgon)		
Automatic level compensator	Type	Centered dual-axis		
	Accuracy	0.5" (0.15 mgon)		
	Range	±5.4' (±100 mgon)		
DISTANCE MEASUREMENT				
Accuracy (ISO)	Prism mode	Standard ²	0.8 mm + 1 ppm (0.0026 ft +1 ppm)	
		Standard	1 mm + 1 ppm (0.003 ft +1 ppm)	
Accuracy (RMSE)	Prism mode	Tracking	5 mm + 2 ppm (0.016 ft + 2 ppm)	
	DR mode	Standard	3 mm + 2 ppm (0.01 ft + 2 ppm)	
		Tracking	10 mm + 2 ppm (0.032 ft + 2 ppm)	
MEASURING TIME				
	Prism mode	Standard	3 s	
		Tracking	0.4 s	
	DR mode	Standard	3-15 s	
		Tracking	0.4 s	
RANGE				
Prism mode (under standard clear conditions ^{3,4})	1 prism	3,000 m (9,800 ft)		
	1 prism Long Range mode	5,000 m (16,400 ft)		
	3 prism Long Range mode	7,000 m (23,000 ft)		
	Shortest range	1.5 m (4.9 ft)		
DR mode		Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
	White card (90% reflective) ⁵	>150 m (492 ft)	150 m (492 ft)	70 m (229 ft)
	Gray card (18% reflective) ⁵	>120 m (394 ft)	120 m (394 ft)	50 m (164 ft)
Shortest range	1.5 m (4.9 ft)			
EDM SPECIFICATIONS (DR HP)				
Light source	Laserdiode 660 nm			
Beam divergence	Horizontal	4 cm/100 m (0.13 ft/328 ft)		
	Vertical	4 cm/100 m (0.13 ft/328 ft)		
SYSTEM SPECIFICATIONS				
LEVELING				
Circular level in tribrach	8/2 mm (8/0.007 ft)			
Electronic 2-axis level in the LC-display with a resolution of	0.3" (0.1 mgon)			
SERVO SYSTEM				
MagDrive servo technology	integrated servo/angle sensor electromagnetic direct drive			
Rotation speed	115 degrees/sec (128 gon/sec)			
Rotation time Face 1 to Face 2	2.6 sec			
Positioning speed 180 degrees (200 gon)	2.6 sec			
Clamps and slow motions	Servo-driven, endless fine adjustment			
CENTERING				
Centering system	Trimble 3-pin			
Optical plummet	Built-in optical plummet			
Magnification focusing distance	2.3×/0.5 m-infinity (1.6 ft-infinity)			
TELESCOPE				
Magnification	30×	Focusing distance	1.5 m (4.92 ft)-infinity	
Aperture	40 mm (1.57 in)	Illuminated crosshair	Variable (10 steps)	
Field of view at 100 m (328 ft)	2.6 m at 100 m (8.5 ft at 328 ft)	Autofocus	Standard	
CAMERA (NOT AVAILABLE IN ALL MODELS)				
Chip	Color Digital Image Sensor	Digital zoom	4-step (1x, 2x, 4x, 8x)	
Resolution	2048 × 1536 pixels	Exposure	Spot, HDR, Automatic	
Focal length	23 mm (0.09 ft)	Brightness	User-definable	
Depth of field	3 m to infinity (9.84 ft to infinity)	Image storage	Up to 2048 × 1536 pixels	
Field of view	16.5° × 12.3° (18.3 gon × 13.7 gon)	File format	JPEG	
POWER SUPPLY				
Internal battery	Rechargeable Li-Ion battery 10.8 V, 6.5 Ah			
External power supply	12 V only external			

Trimble S9/S9 HP

Total station



SYSTEM SPECIFICATIONS cont...

POWER SUPPLY cont...

Operating time ⁶	One internal battery	Approx. 6.5 hours
	Three internal batteries in multi-battery adapter Robotic holder with one internal battery	Approx. 18 hours 13.5 hours
Operating time for video robotic ⁶	One battery	5.5 hours
	Three batteries in multi-battery adapter	17 hours

WEIGHT AND DIMENSIONS

Instrument (Autolock)	5.4 kg (11.35 lb)	Tribrach	0.7 kg (1.54 lb)
Instrument (Robotic)	5.5 kg (11.57 lb)	Internal battery	0.35 kg (0.77 lb)
Trimble CU controller	0.4 kg (0.88 lb)	Trunnion axis height	196 mm (7.71 in)

LASER CLASS (DR PLUS)

LASER CLASS (DR HP)

EDM	Laser class 1	EDM	Laser class 1 in Prism mode, Laser class 2 in DR mode
Laser pointer coaxial (standard)	Laser class 2	Laser pointer coaxial (standard)	Laser class 2
Overall product laser class	Laser class 2	Overall product laser class	Laser class 2

AUTOLOCK AND ROBOTIC SURVEYING

Passive prisms	500 m–700 m (1,640–2,297 ft)	
Trimble MultiTrack™ Target	800 m (2,625 ft)	
Trimble Active Track 360 Target (DR Plus EDM)	500 m (1,640 ft)	
Trimble Active Track 360 Target (DR HP EDM)	100 m (328 ft)	
Autolock pointing precision at 200 m (656 ft) (Standard deviation) ⁴	Passive prisms	<2 mm (0.007 ft)
	Trimble MultiTrack Target	<2 mm (0.007 ft)
	Trimble ActiveTrack 360 Target	<2 mm (0.007 ft)
Shortest search distance	0.2 m (0.65 ft)	
Type of radio internal/external	2.4 GHz frequency-hopping, spread-spectrum radios	
Search time (typical) ⁸	2–10 sec	

FINELOCK

FineLock pointing precision at 300 m (980 ft)	(standard deviation) ⁴	<1 mm (0.003 ft)
	Range to passive prisms (min–max) ⁴	20 m–700 m (65 ft–2,297 ft)
Long Range FineLock (not available in all models)	Minimum spacing between prisms at 200 m (656 ft)	0.5 m (1.65 ft)
	Pointing precision at 2,500 m (8,200 ft) (standard deviation) ⁴	<10 mm (0.039 ft)
	Range to passive prisms (min.–max.) ^{4,9}	250 m–2,500 m (64 ft–8,200 ft)
	Minimum spacing between prisms at 2,500 m (8,200 ft)	0.5 m (1.65 ft)


GPS SEARCH/GEOLock

GPS Search/GeoLock	360 degrees (400 gon) or defined horizontal and vertical search window
Solution acquisition time ¹⁰	15–30 sec
Target re-acquisition time	<3 sec
Range	Autolock & Robotic range limits

OTHER SPECIFICATIONS

Tracklight built in	Not available in all models	Humidity	100% condensing
Operating temperature	–20 °C to +50 °C (–4 °F to +122 °F)	Communication	USB, Serial, Bluetooth ^{®7}
Storage temperature	–40 °C to +70 °C (–40 °F to +158 °F)	Security	Dual-layer password protection, L2P11
Dust and water proofing	IP65	Tracking rate	10 Hz

1 Standard deviation according to ISO17123-3.
 2 Standard deviation according to ISO17123-4.
 3 Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.
 4 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
 5 Kodak Gray Card, Catalog number E1527795.
 6 The capacity in –20 °C (–5 °F) is 75% of the capacity at +20 °C (68 °F).
 7 Bluetooth type approvals are country specific. Contact your local Trimble Authorized Distribution Partner for more information.
 8 Dependent on selected size of search window.
 9 Long Range FineLock can be used with standard FineLock from 20 m.
 10 Solution acquisition time is dependent upon solution geometry and GPS position quality.
 11 Functionality and availability dependent on region.
 Specifications subject to change without notice



Contact your local Trimble Authorised Distribution Partner for more information

NORTH AMERICA
 Trimble Inc.
 10368 Westmoor Dr
 Westminster CO 80021
 USA

EUROPE
 Trimble Services GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC
 Trimble Navigation
 Singapore PTE Limited
 3 HarbourFront Place
 #13-02 HarbourFront Tower Two
 Singapore 099254
 SINGAPORE

